ClearWater Tanks

CLT293 | 293,360 L

Engineered steel liner water tanks designed for reliable performance across a wide range of applications. From rainwater harvesting and stock watering systems to commercial, industrial, and stormwater storage. Built for strength, longevity, and versatility in every environment.

TANK SPECIFICATIONS

Gross Capacity	293,360 L
Diameter	13.03 m
Height	2.2 m
Pad Size | Width	15.03 m
Pad Size | Depth	150mm
After Install | Aggregate	2 m^3
Minimum Water Required On Install	12,500 L
Minimum Sand Required for Pad	33 m^3

TANK INCLUSIONS

- COLORBOND® or ZINCALUME® steel walls & roof
- Roof Trusses, Hot-dipped Galvanised Steel
- Australian made AquaShield Liner - BPA Free
- 1 x 2" Outlet and Valve
- 1 x 4" Overflow
- 1 x Leaf Basket OR 50mm inlet
- 1 x Lockable Manhole
- Bolt Fascia

INCLUSIONS

4"Overflow

1 x 2" Outlet & Valve

Leaf Basket or 50mm Inlet

Lockable Manhole

OPTIONAL EXTRAS

- ☐ Additional 50mm Inlet
- ☐ Additional 50mm outlet with valve
- ☐ Custom inlets and outlet
- ☐ Water level indicator
- ☐ External / internal ladder
- ☐ Dust & vermin proofing
- ☐ Valve with Storz coupling for fire outlet

Internal/External Ladder

Water Level Indicator

BlueScope

AUSTRALIAN MADE AND OWNED

ENGINEER CERTIFIED